

Safety Data Sheet

Ref N° 01 Date: 02/11/2020

I- Product and Company Identification

- a- Product Name : Okougreen
- b- Company address : STAR PLY GABON
GSEZ NKOK LIBREVILLE/Gabon
PLOT N° B2/B1
Bp: 1024
- c- Telephone : (+241) 062 357 222
- d- Email :starplygabon@gmail.com

II- Parts Information

- a- Wood veneer
- b- Bonding Resin

III- HAZARDS IDENTIFICATION

- a- Main hazards of product: N/A
- b- main symptoms related to use or misuse: N/A
- c- Danger pictograms: NA

IV- Description of emergency first aid

- a- Eye contact with sawdust
In case of sawdust contact with the eyes, Rinse yourself with clean water for 15 to 20 minutes, if the situation does not improve, contact your doctor.
- b- contact of sawdust with skin
If sawdust comes into contact with skin, wash with soap and clean water .Remove contaminated clothing
- c- Ingestion : N/A
- d- Inhalation
If you are buried, remove yourself and put yourself in the fresh air, if irritation persists, consult a doctor.

V- Fire –Fighting measures ,explosions and fire prevention

- a- Specific hazard

In case of fire may give rise to hazardous fumes, Okougreen product may ignite if exposed to temperatures exceeding 400 F

These product are combustible and burn if exposed to open flames, high temperature objects ,or oxidizing chemicals

b- Explosion Hazards

Airborne concentrations of finely divided wood and resin dust may arise from wood working and grinding activities. If such wood dust, when it arises, is combined with an ignition source, it can create a fire or explosion hazard if the concentration of wood dust exceeds 40g/m³. This may be prevented by wood working in well ventilated areas.

c- **Flash point** : N/A

d- Inervention methods and stakeholder protections

- In case of ignition of Okougreen products, use water and carbon dioxide powder to fight the flames.
- In order to fight the flames, a firefighter's equipment is recommended then a breathing model to shelter against smoke inhalation

VI- Measures to be taken in the event of accidental dispersal

- a- Personal Precautions :N/A
- b- Environmental Precaution: N/A
- c- Method of cleaning: N/A

VII- Storage, use and handling precautions

a- Technical measures to prevent worker exposure

Wearing handling gloves is recommended for handling Okougreen

b- Recommended and avoided technical measures and storage conditions

Okougreen should be stored in a dry environment and stacked in such a way that no danger is recovered

VIII- Procedures for controlling worker exposure and characteristics of personal protective equipment

While working at the okougreen, wear handling gangs, wear safety glasses when cutting and an anti-dust mask

IX- Physico-chemical property

a- Aspect :

Wood plywood in pink colour

b- Ph

10.5-11.5%

c- Densité

500 g /m³

d- **Freezing point** :N/A

X- Product stability and reactivity

a- Materiel to avoid

Oxidising chemicals

b- Hazardous decomposition products

Stable under normal conditions

XI- Toxicological information

a- Mild skin and eye irritant to sensitive individuals

XII- Ecotoxicology information

Okougreen wants to respect the environment because produced with a glue with low formaldehyde emission, OKOUGREEN is controlled CARB Phase 2 and TSCA Title VI

XIII- Information on waste disposal options

Okougreen is biodegradable, may be suitable for composting or energy recovery

XIV- Information on transport

The transportation of okougreen must be protected from the weather.

XV- Regulation information

a- Symbols :N/A

b- R-phrases : N/A

c- Phrases: N/A

XVI- Other Information

STAR PLY Gabon Gabon to try to put at your disposal an SDS providing you information about the product Okougreen .

For comments or suggestions please contact customer service at starplygabon@gmail.com, tel: +241 062 35 72 22.

Since handling ,use ,and storage of this product is beyond our control STAR PLY Gabon assumes no responsibility and disclaims liability for any loss, damage ,or expense arising there from