

Product: Sundeala K Quality

Issue date: 1 June 2007

Rev Date:

# Product Safety Data Sheet

## Sundeala K & K Colourboard



### 1. Identification

**Description:** Sundeala K and K Colourboard

**Company address:** Middle Mill, Cam, Dursley, Glos GL11 5LQ

**Tel:** 01453 540900

**Fax:** 01453 549085

**E-mail:** sales@sundeala.co.uk

### 2. Composition

**Description:** Rigid sheet material of compressed cellulose fibre forming a "Medium" board manufactured to BS EN 622-3 MBL. Colourboards contain an element of non toxic mineral pigment. No formaldehyde is used in the manufacturing process

### 3. Hazard Identification

**Hazards:** No significant hazard, however board dust when cutting may offer fire hazard if exposed to naked flame

### 4. First-aid Measures

**Eye contact:** Dust from product may cause contamination. Rinse with clean cold water until comfortable. Seek medical attention if necessary.

**Skin contact:** Wash dust from skin with soap and water.

**Ingestion:** wash dust out of mouth with water. Give water to drink. Do not induce vomiting. If large amount has been ingested seek medical attention.

**Inhalation:** Always wear a mask when cutting or sanding the board. Keep area well ventilated.

### 5. Fire-fighting measures

**Extinguishing media:** Water spray, Foam, Dry powder, Carbon Dioxide

**Unsuitable extinguishing media:** None

**Exposure hazards:** Dust will ignite if exposed to naked flame.

**Protective equipment:** Respiration and eye protection in case of smoke. In a fire the product will release oxides of carbon.

### 6. Accidental release measures

Not applicable

### 7 Handling and storage

**Handling:** Handle according to recommended good industrial practice with regard to weight and size of board. Provide adequate ventilation from dust generation when handling large volume of boards. Condition product before use following the recommendations published in Sundeala literature

**Storage:** Store in a stack on a level, flat surface in dry, covered conditions. When installing product break from stack and allow boards to atmospherically condition within the areas of use. Full recommendations are available from published literature.

Product: Sundeala K Quality

Issue date: 1 June 2007

Rev Date:

# Product Safety Data Sheet

**Sundeala K & K Colourboard**



## 8. Exposure controls/ Personal protection

**Environmental measures:** When cutting or sanding make sure there is adequate ventilation.

**Respiratory protection:** Wear a mask when cutting or sanding the board.

**Hand protection:** Industrial gloves if necessary.

**Eye Protection:** Safety goggles to be worn when cutting or sanding the board.

**Skin protection:** barrier cream if sensitive to dust.

## 9. Physical properties

**Physical state:** Solid

**Odour:** Odourless

**pH:** Neutral

**Flammability:** Class D

**Explosive properties:** Not applicable

**Water solubility:** Not applicable

**Relative density:** 500 Kg/m<sup>3</sup>

**Sound absorption coefficient:** 0.15

**Thermal conductivity:** 0.07 W/mK

## 10. Stability and Reactivity

**Conditions to avoid:** Areas of high humidity and unstable, unheated and unconditioned atmospheres

**Materials to avoid:** Oil based paints and solvents

**Hazardous Decomposition products:** In combustion emits carbon oxides.

## 11. Toxicological information

**Eyes:** Unlikely to cause more than a transient stinging from board dust

**Skin:** Unlikely to cause harm to skin on occasional contact from board dust

**Inhalation:** Unlikely to cause any lasting effects from board dust

**Ingestion:** The dust from this product has no known systemic toxicity

Product: Sundeala K Quality

Issue date: 1 June 2007

Rev Date:

# Product Safety Data Sheet

**Sundeala K & K Colourboard**



## 12. Ecological information

Stable product with no known adverse environmental effects

## 13. Disposal considerations

**Waste disposal:** Non Hazardous waste. Waste accepted for landfills or incineration to local authority regulations

## 14. Transport information

No special precautions

## 15. Regulatory information

**Exposure limits:** Recommended workplace exposure limit 5 mg/m<sup>3</sup> from dust when cutting or sanding board

## 16. Other information

H&SE Guidance Note EH40 - Occupational Exposure Limits  
Hazardous Waste regulations  
List of Wastes/European Waste Catalogue (EWC)  
Environmental Agency Technical Guidance WM2  
Landfill Regulations

This information offers typical values and is not a product specification. No warranty expressed or implied is made

This data sheet does not constitute an assessment for "Workplace" risk